

TI-POE24GF-370

24 Ports PoE Ethernet Switch



FEATURES

- ◆ Conforms to IEEE802.3, IEEE802.3u, IEEE802.3af, IEEE802.3at
- ◆ Provide 24 PoE 10/100 Base-TX ports, including 2Gbps Uplink Port
- ◆ Provide 2 SFP Port (1Gbps)
- ◆ IEEE802.3x Flow control
- ◆ Surge protection for each port
- ◆ Max. 15W per port (Total 370W)
- ◆ Managed Switch via Web Browser

SPECIFICATIONS

Item	Description		
Power Supply	Built-in Power Supply		
Voltage Range	AC100V ~ 240V		
Consumption	370W for 24 PoE		
Speed	1-24 port: 10/100Mbps ; G1~G2: Gigabit Combo		
Transmission Distance	100 Meters (328ft) for RJ45; 2 Kilometers 20 Kilometers for SFP Port		
Ethernet Standard	IEEE 802.3, 802.3u, 802.3af/at		
Switching capacity	24+2G for 8.8G		
Transfer Rate	14,880 pps for 10Mbps / 148,800 pps for 100 Mbps / 1,448,000pps for 1000Mbps		
MAC Address	4K MAC address table		
Working Temperature	0° ~ 40° C		
Storage Temperature	-40° ~ 70° C		
Humidity Non-condensing	0 ~ 85%		
Dimension L X W X H	440mm x 200mm x 44mm		
Color	Gray		
Function	-	-	Managed Switch via Web Browser
LINK/ACT	On	Green	The port is connected
	Blinks	-	The port is receiving or transmitting data
	Off	-	The port is not linked successfully with the device
PoE (Powered by 45.78)	On	Orange	Power is being distributed
	Off	-	Power is not being distributed

Application

