

# TA-TM35HN

Ultimate CCTV Test Monitor

Supports AHD/TVI/CVI/CVBS



## KEY FEATURES

- Video Signal Test
- HD Coaxial Signal Test
- Video Signal Level Test
- PTZ Controller
- Enhanced Color Bar Generator
- DC12V 1A Output Power
- Audio Testing
- Cable Tester
- PTZ Address Scanning
- DATA Monitor
- LED Lamp
- UTP Tester

TA-TM35HN	
Signal Mode	NTSC/PAL (Auto adapt)
Display	3.5 inch digital TFT-LCD, 480 (RGB) x 320 Res.
LCD adjustment	Brightness, Contrast, Saturation adjustable
Video IN/OUT	1 channel BNC input & 1 channel Output
Video Output Mode	1.0 Vp-p
Level Test	Video signals measured in IRE or mV
Communication	Support RS232 and RS485
PTZ Protocol	Compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic, Lilin, Yean, etc.
Baud Rate	600, 1200, 2400, 4800, 9600, 19200, 57600, 115200bps
UTP Cable Test	Test UTP cable connection status and display in the screen. Read the number of the test box.
DC12V Power Output	Output DC12V1A power for camera
Audio Input Test	Test the pickup and other audio equipments
Data Monitor	Captures and analyzes the command data
Power Adaptor	DC 5V (1.5A)
Battery	Built in 3.7V Lithium polymer battery, 3000mAh
Rechargeable	After charging 3-4 hour, working time lasts 11 hours
Low Consumption	Energy saving technology. Battery icon display
Working Temperature	-10° - 50° C
Working Humidity	30% - 90%
Dimension	194 x 112 x 48mm
Weight	540g