

# TI-NC405-TDA-28

5MP IR Dome IP Camera

# FREEDOM



## KEY FEATURES

- Max. 5MP (2592\*1944)
- Network Camera (IP)
- H.265/H.264 dual-stream media service
- Easy-to-use Plug & Play
- Low lux / Day/Night (ICR), DWDR
- Lightning protection 4000V
- 12 VDC & PoE / Water-proof IP66
- 18pcs SMD IR 90FT
- 2.8mm Fixed Lens
- Internal Microphone

TI-NC408-2XDA-28		
Camera	Image Sensor	1/2.7" 5MP OS05A10 CMOS
	Effective Pixels	2592(H)×1944 (V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	WDR	Digital WDR
	White Balance	Auto/Manual
	AGC/BLC/HLC	Support
	DNR	2D/3D DNR
	Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Flip
Encode	Video Standard	H.264/H.265
	Video Resolution	Main Stream:15fps@5MP(2592x1944),25fps@4MP/3MP,30fps@1080P/720P Sub Stream: D1/VGA(640x480)/360P/QVGA@30fps
	Video Bitrates	32Kbps - 8Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a, optional Mic
	OSD Overlay	Title and Time overlay
IR Led	IR Led	18pcs SMD IR Led
	IR Distance	90 ft
Lens	Focal Length	2.8mm Fixed lens
Optional	Optional Functions	PoE, Audio, etc.
Network Services	Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
	P2P	Yes
	Web	IE, Firefox, (32bit ESR), etc.
	Media	CMS, Android, iOS
	ONVIF	17.06 compatible
General	Network Port	1-RJ45, 100Mbps, PoE optional
	Power Supply	12 VDC ± 10%
	Power Consumption	< 8 W
	Operating Temp.	-22°F - 140°F, 10% - 90%RH

## DIMENSIONS

