

TI-NC405-4VDZA

5MP IR Dome IP Camera



KEY FEATURES

- Max. 5MP (2592*1944)
- Network Camera (IP)
- H.265/H.264 dual-stream media service
- Easy-to-use Plug & Play
- Low lux / Day/Night (ICR), DWDR
- Lightning protection 4000V
- 12 VDC & PoE / Water-proof IP66
- 18pcs SMD IR 90FT
- 2.8-12mm VF, Auto Focus Lens
- Internal Microphone

TI-NC405-4VDZA		
Camera	Image Sensor	1/2.7" 5MP OS05A10 CMOS
	Effective Pixels	2592(H)×1944 (V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100000s
	Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
	Day/Night	Auto/Color/(B/W)/Timing
	WDR	Digital WDR
	White Balance	Auto/Manual
	AGC/BLC/HLC	Support
	DNR	2D/3D DNR
	Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Flip
Encode	Video Standard	H.264/H.265
	Video Resolution	Main Stream:15fps@5MP(2592x1944),25fps@4MP/3MP,30fps@1080P/720P Sub Stream: D1/VGA(640x480)/360P/QVGA@30fps
	Video Bitrates	32Kbps - 8Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a, optional Mic
	OSD Overlay	Title and Time overlay
IR Led	IR Led	18pcs SMD IR Led
	IR Distance	90 ft
Lens	Focal Length	2.8-12mm Motorized lens
Optional	Optional Functions	PoE, Audio, etc.
Network Services	Protocol	HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.
	P2P	Yes
	Web	IE, Firefox, (32bit ESR), etc.
	Media	CMS, Android, iOS
	ONVIF	17.06 compatible
General	Network Port	1-RJ45, 100Mbps, PoE optional
	Power Supply	12 VDC ± 10%
	Power Consumption	< 8 W
	Operating Temp.	-22°F - 140°F, 10% - 90%RH

DIMENSIONS

