

TI-NC405-PIR

5MP IP Hidden IR Camera with PoE



KEY FEATURES

- 1/3" Sony CMOS sensor
- 2688(H) x 1520(V)
- Low illumination 0.01Lux
- Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT
- D-WDR, Mirror, rotate, Defogging
- OSD Overlay, Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Support multiple WEB browsers (IE, Firefox 32bit ESR)
- PC Client, Mobile APP remote access.
- 100mbps network port(Ethernet), IEEE802.3af PoE
- IP54
- 18pcs SMD IR Leds, IR distance 45 ft
- 3.7mm Pinhole Fixed Lens



TI-NC405-PIR		
Camera	Image Sensor	1/3" Sony CMOS sensor
	Effective Pixels	2688(H) x 1520(V)
	Electronic Shutter	AUTO, 1/25s ~ 1/100,000s
	Min. Illumination	0.1Lux@F1.2(AGC ON), 0 Lux with IR
	Day / Night	Auto / Color / BW / Timing
	WDR	Digital WDR
	White Balance	Auto
	AGC / BLC	Support
	DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate	
Video and Audio	Video Standard	H.265 / H.264
	Video Resolution	Main Stream: 15fps@5MP (2592x1944), 20fps@4MP (2592x1520), 25fps@3MP / 1080P / 720P Sub Stream: VGA (640x480) / 360P / QVGA@25fps, etc.
	Video Bit Rate	32Kbps - 8Mbps, VBR/CBR
	Audio Standard	G.711-u/G.711-a
IR LED	IR LED	12 pcs IR LEDs
	IR Distance	45 ft
Lens	Focal Length	3.7mm Pinhole Fixed Lens
Optional	Optional Features	PoE, Audio, etc.
Network Services	Protocol	HTTP / RTSP / FTP / NFS / SMTP / DHCP / NTP, etc.
	P2P	Yes
	Web	IE, Firefox 32bit ESR
	Media	CMS, Android, IOS
	ONVIF	17.06 compatible
General	Network Port	1-RJ45, 100Mbps, PoE optional
	Power Supply	12VDC ±10%
	Power Consumption	< 5W
	Operating Temp.	-22°F to +140°F, 10%-90%RH