

TI-NC405-VBZ

5MP Motorized IP Camera



KEY FEATURES

- 1/3" CMOS Sensor
- 2592 x 1944 Resolution
- Low Illumination 0.1 Lux
- Day/Night, AWR/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT, D-WDR, Defog
- OSD, Motion Detection, Privacy Mask
- RTSP and Onvif 2.6 compatible with many third-party NVR
- H.264 / H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Lightning protection 4000V
- Strong water-proof housing IP66
- 3pcs High Power Array IR LED, IR distance 40-50m
- HD 2.8-12mm AF lens

ACCESSORIES



TI-DSW8
Wall Mount
Bracket

TI-NC405-VBZ		
Camera	Image Sensor	1/3" Sony CMOS
	Effective Pixels	5MP
	Electronic Shutter	auto, 1/25S ~ 1/100,000s
	Min. Illumination	0.01 lux@(F1.2, AGC ON), 0 lux with IR
	Day / Night	Auto / Color / B/W / Timing
	WDR	Digital WDR
	White Balance	Auto / Manual
	BLC	Support
	DNR	2D / 3D DNR
	Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror, Rotate
Encode	Video Standard	H.264 / H.265
	Video Resolution	Main Stream: 15fps@5MP (2592x1944), 20fps@4MP (2592x1520), 25fps@3MP / 1080P / 720P Sub Stream: VGA / 360P@25fps, etc.
	Video Bit Rate	32 Kbps ~ 8 Mbps, VBR/CBR
	Audio Standard	G.711-u / G.711-a
	OSD Overlay	Title and Time overlay
IR	IR LED	24 pcs SMD IR LED
	IR Distance	40-50m
Options	Optional Function	PoE, Audio
Lens	Focal Length	2.8-12mm AF Lens
	Protocol	HTTP / RTSP / FTP / NFS / SMTP / DHCP / NTP, etc.
Network Services	P2P	Yes
	Web	IE, Firefox 32bit ESR
	Media	CMS, Android, IOS
	ONVIF	2.6 compatible
General	Network Port	1-RJ45, 100Mbps, PoE optional
	Power Supply	12VDC ±10%
	Power Consumption	< 10W
	Operating Temperature	-20°C to +60°C, 10%-90%RH

DIMENSION

