

DS-KAD606



SPECIFICATIONS

FEATURES & NOTES

- ◆ Built-in 24V DC voltage-stabilized switching mode power supply
- ◆ Eight RJ45 interfaces, including six adaptive 10/100M LAN interfaces supporting network cable powering and two adaptive 10/100M cascading LAN interfaces
- ◆ IEEE802.3, IEEE802.3u, IEEE802.3x
- ◆ Storing and forwarding function
- ◆ VLAN technique
- ◆ Over 1000,000h mean time between failure
- ◆ Operating temperature range: from -30° C to +70° C
- ◆ Suitable for wall mounting

Parameters	Model	DS-KAD606
Interface Number		Eight 10/100M Interfaces
Interface Type		RJ45, Full/Half-Duplex, MDI/MDI-X Self-Adaptive
Standard		IEEE802.3, IEEE802.3u, IEEE802.3x
Processing Type		Storing and Forwarding
Flow Control		IEEE802.3x (Full-Duplex), Back Pressure (Half-Duplex)
Priority queue		Four
MAC Address List		8K
Internal Buffer		1 Mbit
Power supply		AC 220 V
Power Dissipation		<3 W
Operating Temperature		-30° C TO +70° C (-22° F to 158° F)
Operating Humidity		5 to 95%, No Condensation
Size		275.2 mm (L) x 92 mm (W) x 102.2 mm (H)
Certification		FCC, CE

TYPICAL APPLICATION

