

THK-NC328-MB

8MP Mini Bullet Camera



KEY FEATURES

- 8MP Mini Bullet Camera
- 1/2.5" Progressive Scan CMOS
- 2.8 mm Fixed Lens / 100ft IR range
- H.265/H.264
- 3D DNR, WDR (120dB), BLC, TDN
- IP67 / Vandal Proof / DC 12V & PoE
- ONVIF Profile (S,G)

THK-NC328-MB		
Camera	Image Sensor	1/2.5" Progressive Scan CMOS
	Min. Illumination	Color: 0.01 lux @(F1.2, AGC ON), 0 lux with IR
	Shutter Speed	1/3 s to 1/100,000 s
	Slow Shutter	Support
	Lens	2.8 mm, horizontal field of view: 102°
	Lens Mount	M12
	Iris	F2.0
	Day & Night	IR cut filter
	DNR	3D DNR
	Wide Dynamic Range	120dB
3-Axis Adjustment		Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360°
Compression Standard	Video Compression	Main stream: H.265/H.264 Sub stream: H.265/H.264/MJPEG Third stream: H.265/H.264
	H.264 Type	Main Profile/High Profile
	H.264+	Support
	H.265	Main Profile
	H.265+	Support
	Video Bit Rate	32 Kbps to 16 Mbps
Image	Max. Resolution	3840 × 2160
	Main Stream	50Hz: 20 fps (3840 × 2160), 25 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720) 60Hz: 20 fps (3840 × 2160), 30 fps (2560 × 1920, 2560 × 1440, 1920 × 1080, 1280 × 720)
	Sub Stream	50Hz: 25fps (640 × 360, 352 × 288) 60Hz: 30fps (640 × 360, 352 × 240)
	Third Stream	50Hz: 25fps (1280 × 720, 640 × 360, 352 × 288) 60Hz: 30fps (1280 × 720, 640 × 360, 352 × 240)
	Image Enhancement	BLC/3D DNR
	Sub Stream	Support rotate mode. Brightness, contrast, saturation, and sharpness are adjustable via web browser and client software
	ROI (Region of Interest)	Support 1 fixed region for mainstream and sub stream separately
	Day / Night Switch	Auto / Scheduled
Network	Network Storage	Support microSD/SDHC/SDXC card (128G) local storage, NAS (NFS,SMB/CIFS), ANR
	Alarm Switch	Motion Detection, Tampering Alarm, Network Disconnected, IP Address Conflict, Illegal Login, HDD full, HDD error
	Day / Night Switch	TCP/IP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6
	Standard	ONVIF (PROFILE S, PROFILE G), PSIA, CGI, ISAPI
	General Function	One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter

THK-NC328-MB

8MP Mini Bullet Camera



KEY FEATURES

- 8MP Mini Bullet Camera
- 1/2.5" Progressive Scan CMOS
- 2.8 mm Fixed Lens / 100ft IR range
- H.265/H.264
- 3D DNR, WDR (120dB), BLC, TDN
- IP67 / Vandal Proof / DC 12V & PoE
- ONVIF Profile (S,G)

THK-NC328-MB		
Interface	Communication Interface	1 RJ45 10M/100M self-adaptive Ethernet port
	On-board Storage	Built-in microSD/SDHC/SDXC slot, up to 128 GB
Smart Feature Set	Behavior Analysis	Line crossing detection, intrusion detection, unattended baggage detection, object removal detection
	Line Crossing Detection	Cross a pre-defined virtual line, up to 1 pre-defined virtual lines supported
	Intrusion Detection	Enter and loiter in a pre-defined virtual region, up to 1 pre-defined virtual regions supported
	Object Removal Detection	Objects removed from the pre-defined region, such as the exhibits on display.
	Unattended Baggage Detection	Objects left over in the pre-defined region such as the baggage, purse, dangerous materials
	Face Detection	Human face appears in the image can be detected and trigger linkage method
General	Operating Conditions	-22 °F to +140 °F, Humidity 95% or less (non-condensing)
	Power Supply	12 VDC ± 25%, 7W PoE(802.3af, class 3), 7.5W
	IR Range	Up to 100ft
	Protection Level	IP67
	Dimensions	Camera: $\Phi 2.76" \times 6.1"$ Package: $8.5" \times 4.76" \times 4.65"$
	Weight	Camera: 0.9 lbs

DIMENSIONS

