

5MP Elevator Camera



MODEL **TA-EV5TVF6TQ**



KEY FEATURES

- 4 IN 1 (TVI/AHD/CVI/CVBS)
- Corner Camera
- 5MP : 2592 × 1944@20fps
- 2.8mm Fixed Lens
- 0.01 Lux (F1.2, AGC ON)
- DV 12V
- Indoor Use Only



TA-EV5TVF6TQ

5MP Elevator Camera

SPECIFICATIONS

Specifications	Model	TA-EV5TVF6TQ
Image Sensor		5MP CMOS Image Sensor IMX335 + FH8558M
Signal System		NTSC
Effective Pixels		2592(H) × 1944(V)
Min. Illumination		0.01 Lux @ (F1.2,AGC ON), 0 Lux with IR
Shutter Time		1/25(1/30) s to 1/50,000 s
Lens		Board Lens 2.8mm
Lens Mount		M12
Adjustment Range		Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day& Night		IR cut filter with auto switch
Video Frame Rate		2592 × 1944@20fps
HD Video Output		AHD / TVI / CVI / CVBS Output
Synchronization		Internal Synchronization
S/N Ratio		More than 62 dB
Up the Coax		Support
Operating Conditions		-20 °C ~ 60 °C (-20 °F ~ 140 °F) Humidity 90% or less (non-condensing)
Power Supply		12 VDC ± 15%
Power Consumption		Max. 4W
IR Range		Up to 5 m
Dimension		197 X 172 X 65 mm
Weight		550g