

# 32CH 4K NVR




## MODEL **TI-NR432N2**

### KEY FEATURES

- Support Ultra 265/H.265/H.264 video formats
- 32-channel input
- Third-party IP cameras supported with ONVIF conformance: Profile S, Profile G, Profile T
- Support 2-ch HDMI, 1-ch VGA, HDMI2 at up to 4K(3840x2160) resolution
- HDMI1/VGA and HDMI2 independent outputs provided
- Up to 12 Megapixels resolution recording
- 4 SATA HDDs, Up to 10TB for each HDD
- Various fisheye dewarping modes for live view and playback for both web interface and GUI
- Support for 12V Power output
- Plug & Play with up to 16 independent PoE network interfaces
- ANR technology to enhance the storage reliability when the network is disconnected
- Support cloud upgrade

### PHYSICAL INTERFACE



# TI-NR432N2

## 32CH 4K/8MP Non-PoE NVR with 4pcs SATA

### SPECIFICATIONS

Model	TI-NR432N2
<b>Video/Audio Input</b>	
IP Video Input	32-ch
Two-way Audio Input	1-ch, RCA
<b>Network</b>	
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Remote Users	128
Protocols	P2P, UPnP, NTP, DHCP, PPPoE
<b>Video/Audio Output</b>	
HDMI/VGA Output	HDMI1/VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
	HDMI2: 4K (3840x2160)/60Hz, 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
	Recording Resolution
Audio Output	1-ch, RCA
Synchronous Playback	16-ch
Corridor Mode Screen	3/4/5/7/9/10/12/16/32
<b>Decoding</b>	
Decoding format	Ultra 265, H.265, H.264
Live view/Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/2CIF/CIF
Capability	3 x 12MP@25, 4 x 4K@30, 8 x 4MP@30, 16 x 1080p@30, 32 x 960p@25
<b>Hard Disk</b>	
SATA	4 SATA interfaces
Capacity	up to 6TB for each HDD
<b>External Interface</b>	
Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet Interfaces
Serial Interface	1 x RS485
USB Interface	Front panel: 1 x USB2.0
	Rear panel: 1 x USB2.0, 1 x USB3.0
Alarm In	16-ch
Alarm Out	4-ch
<b>General</b>	
Power Supply	12V DC
	Power Consumption: ≤ 12W (without HDD)
Working Environment	+14°F~+131°F (-10°C~+ 55°C), Humidity ≤ 90% RH (non-condensing)
Dimensions (WxDxH)	440mm × 344mm × 50mm (17.3" × 13.5" × 2.0")
Weight (without HDD)	≤ 3.14Kg (6.92lb)