

# 4Ch Turbo TVI DVR



## MODEL TA-HD TVI504A



### KEY FEATURES

- HDTV/ AHD/ CVI/ CVBS/ IP video input
- Max. 6 IP cameras input (Up to 8 MP)
- 5MP/4MP HDTV video input and live view
- H.265 Pro+/H.265 Pro/H.265 video compression
- Full channel recording at up to 5MP resolution
- Simultaneous HDMI/VGA output
- HDMI output at up to 4K (3840x2160) Resolution (16ch, 8ch only)
- Separate CVBS output
- 1 SATA interface (up to 10TB capacity per HDD)
- Supports line crossing detection and intrusion detection on all channels
- VCA information overlay in live view and smart playback

# TA-HDTVI504A

## 4Ch Turbo TVI DVR

### SPECIFICATIONS

Model	TA-HDTVI504A		
<b>Recording</b>			
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264		
Encoding resolution	5MP/4MP/3MP/1080p/720p/WD1/4CIF/VGA/CIF		
Frame rate	Main stream: 5MP@12fps/4MP@15fps/3MP@18fps 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)		
	Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N)		
Video bit rate	32 Kbps to 10 Mbps		
Dual-stream	Support		
Stream Type	Video, Video & Audio		
Audio Compression	G.711u		
Audio Bit rate	64 Kbps		
<b>Video and Audio</b>			
IP video input2	2-ch (up to 6-ch)	Up to 8MP resolution	Support H.265+/H.265/H.264+/H.264 IP cameras
Analog video input	4-ch, BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection		
AHD input	5MP, 4MP, 1080p25, 1080p30, 720p25, 720p30		
HDCVI input	4MP, 1080p25, 1080p30, 720p25, 720p30		
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480		
HDMI/VGA output	1-ch, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz		
Audio input	4-ch, RCA (2.0 Vp-p, 1 KΩ)		
Audio output	1-ch, RCA (Linear, 1 KΩ)		
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the rst audio input)		
Synchronous playback	4-ch		
<b>Network</b>			
Remote connections	32		
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF		
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface		
<b>Auxiliary Interface</b>			
SATA	1 SATA interface		
Capacity	Up to 10 TB capacity for each disk		
Serial interface	RS-485 (half-duplex)		
USB interface	2 × USB 2.0		
Alarm in/out	4/1		

# TA-HDTV1504A

## 4Ch Turbo TVI DVR

### SPECIFICATIONS

Model	TA-HDTV1504A
<b>General</b>	
Power supply	12 VDC
Consumption (without HDD)	≤ 10 W
Working temperature	+14 °F to +131 °F (-10 °C to +55 °C)
Working humidity	10% to 90%
Dimensions (W × D × H)	315 × 242 × 45 mm (12.4 × 9.5 × 1.8 inch)
Weights (without HDD)	≤ 1.16 kg (2.6 lb)

### DIMENSIONS

