

IP Video Intercom Door Station



MODEL **DS-KB8113-IME1**

KEY FEATURES

- Communicates with Indoor Station
- Access control function supports multiple door opening modes
- 16ft (5m) IR Range
- High- Performance SOC Processor
- IK9 and IP66
- Power-over-Ethernet (PoE 802.3af)

DS-KB8113-IME1

IP Video Intercom Door Station

SPECIFICATIONS

Model	DS-KB8113-IME1
System Parameters	
Processor Operation System	High-performance embedded SOC processor Embedded Linux operaton system
Camera Parameters	
Image Sensor Light Sensitivity Lens Field of View Field of View Adjustment	1/3" progressive scan CMOS, color, day/night Low Illumination Pihole f/3.47 mm, f /2.5 80° (horizontal), 44° (Vertical) -50° to 50°
Video Parameters	
Video compression standard Video Streaming Resolution Video Frame Rate Video Bit Rate Auto-flicker Frequency Wide Danamic Range Image Setting	H.265 Dual stream Main stream : 1280 x 720, Sub-stream : 640 x 480 PAL : 25fps, NTSC : 30fps Main stream : 32 kbps to 4096 kbps, SUB-STREAM : 32 KBPS TO 2048 KBPS 50 HZ, 60 HZ Digital WDR, auto-switch, day/on, night/off Color, brightness, contrast, sharpness, saturation, video standard, OSSD display
Audio Parameters	
Audio Streaming Audio Input Audio Output Audio Compression Standard Audio Compression Rate Audio Quality	To-way, full duplex Built-in omnidirectional microphone Built-in loudspeaker G. 711U 64 kbps Noise suppression and echo cancellation
Light Supplement	
Light supplement Mode Wavelength Control	IR supplementnt, IR range : 16ft (5m) 940mm Auto on/off, time on/off
Network Parameters	
Ethernet Network protocol Network connection Mode Door-Unlocked Duration	10/100 Mbps self-adaptive Ethernet RTSP, TRP, ONVIF, ISAPI, NTP, HTTP, HTTPS, DHCP, FTP, SMTP DHCP, static IP address 1s to 255s
Alarm Parameters	
Alarm Input	Dppr agnetic alarm
Device Interfaces	
Network Interface I/O input I/O Output	1 RJ-45 10/100 Mbps self-adaptive ethernet interface 1 1 relay output
Event Actions	
Event File Uploading Email Notification	Motion detection, picture capturing, call buttom pressing FTP Login succeeded via software of Web
General	
Material Impact protection Ingress Protection Level Certifications Power Supply Power Consumption Working Temperature Working Humidity Dimensions) L x W x H) Weight Included Accessories	Wall Mounting shield : zine alloy, Front panel : zinc alloy, Rear panel : aluminum alloy, Wall mounting plate : secc IK9 IP66 CE, FCC, UL 60950-1 PoE (Power over Ethernet), 12DVC Maximum 12W -22° to + 122° F(-30° C) 10% ~ 90% 6.37" x 2.92" x 2.09" (161.9 mm x 74.1 mm x 53.2 mm) 1.70 lb (773g) Quick start guide, CD with user manual and software, wall mounting plate, wall mounting shield, screw package, screw driver

DS-KB8113-IME1

IP Video Intercom Door Station

DIMENSION

