


# 8MP Stitched 180° Panoramic Network Camera



MODEL **TI-NCT08SP**




## KEY FEATURES

- Four 2MP video modules to stitch one 8MP (4096x1800), 180° panoramic view stream
- True starlight technology (0.008lux@F2.0 AGC on) provides vivid color at most scenarios
- 20m Smart IR provides clear and uniform B/W image under no light conditions
- DWDR, 3D DNR, BLC, HLC
- Recognizes max. 50 faces/s within a public area
- Alarm triggered by multi-rules: line crossing, intrusion, device error
- 5 zones of e-PTZ, 4 zones of privacy masks, and custom logo support.
- ONVIF specifications, interoperability between network video products, regardless of manufacturer
- Interface: RJ45, SD Card, Alarm, Audio, RS485
- -30°C~60°C(-22°F~140°F), IP67, IK10, Metal body
- Support both PoE(802.3.af) and DC12V
- One IP, one cable, reducing total fees



## APPLICATION

- Public area safety: Railway station, Airport, Cathedral, City mall, Plaza, School, Conference room, etc.



# TI-NCT08SP


## 8MP Stitched 180° Panoramic Network Camera

### SPECIFICATIONS


Specifications	Model	TI-NCT08SP
<b>Camera Module</b>		
Image sensor		1/2.8" progressive scan CMOS image sensor x 4
Mini. Illumination		Color:0.008Lux @(F2.0,AGC ON) ; B/W:0.008Lux @(F2.0,AGC ON) ; 0Lux with IR
Image setting		Flip, Mirror, Saturation, Brightness, Contrast, Sharpness, AGC, and AWB adjusted by client software/browser
Shutter Speed		1/1 s – 1/10,000 s
White Balance		Auto/Manual/Indoor/Outdoor
Gain		Auto/Manual
Day & Night		IR Cut filter
Digital Zoom		16x
Privacy Mask		4 Programmable privacy masks
3D DNR		Auto/Manual
BLC		Yes
HLC		Yes
WDR		D-WDR
Defog		Electronic
EIS		Yes
Regional Exposure		No
Picture overlay		Logo picture could be overlaid on video
<b>Lens</b>		
Focus length		3.2mm lens x 4
Aperture		F2.0
FOV		Panoramic image : Horizontal FOV : 180° ; Vertical FOV: 85°
Working distance		1.0m ~ INF
<b>IR</b>		
IR Range		20m radius
Smart IR		Yes
<b>Network</b>		
Max Resolution		4096x1800@25/30fps
Main stream		4096 x 1800, 3840 x 1680, 2880 x 1264(1~30fps)
Sub stream:		2048 x 896, 704 x 320(1~30fps)
Third stream:		704 x 320 ( 1~30fps )
SVC		Yes
Video compression		Smart H.265/H.264/MJPEG
Audio compression		G.711 A/U
Audio Enhancement		Not support
Protocols		HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP,DNS, DDNS, NTP, RTSP, RTP, TCP/IP, UDP, IGMP, ICMP,DHCP, PPPoE
Simultaneous live view		Up to 6 channels
User / Host		Up to 16 users, 3 levels: Administrator, Advanced User and Normal User

<b>Network</b>	
Security Measures	User authentication (ID and PW), Host authentication (MAC address); HTTPS encryption, IEEE802.1x port-based network access control; IP address filtering
<b>Smart Features</b>	
Basic event	Motion detection(panorama and original modes support), video tampering alarm, exception(network disconnected, IP address conflict, SD full, SD error)
Face recognition	Max 50 human faces per second(default off) (V 5.01 and later supports)
Face comparison	Default off
Smart Detection	Intrusion detection, line crossing detection, region entrance detection, region exiting detection, target counting
Alarm Linkage	Upload to FTP/Memory card, notify surveillance center,send email, trigger alarm output, trigger recording, trigger capture
<b>System Integration</b>	
Alarm Interface	1CH alarm input; 1CH alarm output
Audio Interface	1CH audio input, 2 to 2.4V[p-p] 1kΩ±10% ; 1CH audio output (line out), impedance: 600Ω
Network Interface	1 RJ45 10M/100M Adaptive Ethernet (Support PoE 802.3.af)
CVBS	Not support
RS 485	Pelco-D / P protocol, custom protocols available
Storage	Built-in memory card slot, support microSD/SDHC/SDXC, up to 256G
USB3.0	Not support
Fiber Optical	Not Support
GIS	Not Support
API	ONVIF, support TVT SDK and third-party management platform
Client	VMS-9000 and the third-party client
Web Browser	IE8-11 (NOT support Safari /Firefox /Chrome)
<b>General</b>	
Power	DC12V, PoE (802.3.af), (Max 12.9W, include IR on )
Working Condition	-30°C~60°C (-22°F~140 °F), 90%RH less (non-condensing),cold start at -20°C
Storage Condition	-40°C~70°C ; ≤ 95%RH
Protection	IP 67, IK 10, 6000VLightning Protection, Surge Protection and Voltage Transient Protection
Material	Aluminum Alloy ; PC
Angle Adjustment	Pan:0~360°; Tilt: 0~90°; Rotation: 0~360°
Dimensions	LxWxH= 288.4mmx159.7mmx137.7mm (11.35" x 6.29" x 5.42")
Weight	Approx. 2.1Kg(4.63lb)
Certification	CE, FC, IK10, IP67
Environment Protection	Complies with Directive EU RoHS, WEEE, Directive 94/62/EC and REACH

### DIMENSIONS



### ACCESSORIES (Optional)



TD-YXH0207 Wall Mount



TD-YXH0207+YZJ0407 Wall Mount



TD-YXH0207+YZJ0811 Ceiling Mount



DC12V3A Power Adapter