

5MP Elevator Camera



MODEL _ **TI-NC405-EV28**

KEY FEATURES

- High quality imaging with 5 MP resolution
- Efficient H.265/ MJPG compression technology
- ICR auto switch, true day / night vision
- 3D DNR, DWDR, HLC, BLC, Defog, NIR
- OSD Overlay, Motion Detection, Privacy Mask
- 1 pcs SMD Array IR Leds, upto 60 ft (20m) IR night view distance
- 2.8mm Fixed Lens
- DC12V/PoE power
- Indoor Only
- Support remote monitoring by smart phones & tablet PCs with iOS and Android OS

TI-NC405-EV28

5MP Elevator Camera

SPECIFICATIONS

Model	TI-NC405-EV28
Camera	
Signal System	5MP Progressive Scan CMOS
Lens	2.8mm lens
Lens Mount	M12
Day& Night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Min.illumination	Color: 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR on
Electronic Shutter	AUTO, 1/25s - 1/100000s
Wide Dynamic Range	DWDR
White Balance	Auto /Manual
AGC/BLC/HLC	Support
Other	Multi-Line OSD, Motion Detection, Privacy Mask, Mirror
Compression Standard	
Video Compression	H.265/MJPEG
Video bit rate	32Kbps~8Mbps
Triple Streams	YES
Image	
Max. Image Resolution	2944x1656
Frame Rate	50 Hz: 12 fps (2944x1656) 60 Hz: 15 fps (2944x1656)
Sub Stream:	50 Hz: 25 fps(3840 x 2160) 60 Hz: 30 fps(3840 x 2160)
Network	
Protocols	Line Crossing, Intrusion Detection, Motion detection, Dynamic analysis, Tampering alarm, Network disconnect , IP address conflict, Storage exception
Protocols	TCP/IP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTSP,RTCP, NTP,UPnP,SMTP,IPv6
General Function	Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering
System Compatibility	ONVIF (Profile S, Profile G),ISAPI
General	
Operating Conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 VDC ± 25% POE
Weather Proof	Indoor Only
IR Range	N/A
Dimensions	4.33 x 3.54" (110 x 90mm)
Weight	550g