


5MP 4-in-1 Dome Camera



MODEL **TA-E5TVV9TQ5-W/Gr**



KEY FEATURES

- 4-in-1 HDTV/HDCVI /AHD / CVBS optional output
- UHD resolution 20fps@2560×1944P CMOS sensor
- Ultra low illumination 0.05Lux
- Up to 300M long distance and high speed real time monitoring
- OSD menu control up the coaxial cable (UTC)
- Low light and perfect night vision
- Day/Night (ICR), AWB, AGC, DNR
- Lightning protection
- Strong water-proof housing, IP66
- 18PCS SMD IR Leds, IR distance 20-30 meters
- HD 2.8-12mm Varifocal lens

TA-E5TVV9TQ5-W/Gr

5MP 4-in-1 Dome Camera

SPECIFICATIONS

Model	TA-E5TVV9TQ5-W/Gr
Camera	
Image Sensor	1/2.5" CMOS
Chipset	C18+FH8538E
Effective Pixels	2592(H)×1944 (V)
Video Resolution	TVI/AHD: 20 fps@2560×1944P, CVI 30 fps@2560×1440P, adjustable
Electronic Shutter	AUTO, 1/25 - 1/50,000s
Min. Illumination	0.05Lux@F1.2(AGC ON), 0Lux IR on
Video System	PAL/NTSC
Video Output	1 channel, HDCVI / HDTVI/AHD/CVBS , adjustable
Video Switch	DIP switch
Day & Night	Auto/Color/(B/W)/EXT
White Balance	ATW/Manual
DNR	2D NR
OSD Menu	Multiple languages OSD menu control up the coaxial cable (UTC)
IR Led	
Warm Led	18pcs SMD IR LEDs
Distance	20-30 M
Lens	
Focal length	2.8mm fixed lens
General	
Power Supply	12 VDC ± 10%
Power Consumption	< 5 W
Operating Temp	-24.8°F ~ 140°F (-30°C-(+60)°C), 10%-90%RH

PHYSICAL INTERFACE

