

# 16CH Hybrid DVR




MODEL **TD-2168P-N2**



## KEY FEATURES

- Supports 16 CH TVI / AHD /CVI 5MP / 4MP / 1080P / 720P / WD1 video input Supports 8 CH 5MP / 4MP / 3MP / 1080P / 960P / 720P IP video input
- 8CH analog video input can be switched to 8CH IP video input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by mouse
- Multi-mode recording: manual / timed / sensor /motion / AI recording Playback : 16 CH simultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Authorization management, log review and device status review
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS

## DIMENSION



# TD-2168P-N2

## 16CH Hybrid DVR

### SPECIFICATIONS

Model	TD-2168P-N2
<b>Video</b>	
Analog Video Input	BNC × 1 6 BNC interface (1.0Vp-p; 75Ω) TVI/AHD/CVI:5MP@20fps; 4MP/3MP/1080P/720P/WD1@30fps
IP Video Input	8CH (up to 16CH) Up to 5MP@30fps
Total Input	24CH
Output	HDMI × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 BNC × 1 : CVBS ( used as the main or spot output )
Compression	H.264/H.265/H.265+
Multi-screen Display	1 / 4 / 6 / 8 / 9 / 13 / 16 / 25
<b>Audio</b>	
Input	RCA × 1
Output	RCA × 1 (linear, 600Ω)
Two-way audio	Take up channel one audio input
Compression	G.711(U/A)
<b>Record</b>	
Resolution	5MP Lite/4MP Lite/1080P/1080P Lite/720P/WD1
Frame Rate	Analog Channel: 5MP Lite:10fps; 4MP Lite/1080P:12fps(PAL)/15fps(NTSC) 1080P Lite/720P/WD1/D1: 25fps (PAL)/30fps (NTSC) IP Channel: 25fps (PAL)/30fps (NTSC)
Bit Rate	32Kbps ~ 5Mbps
Mode	Manual, timer, motion, smart event
<b>Playback</b>	
Playback	16 CH
Search	Time slice / time / event / tag search
Smart Search	Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
Function	Play, pause, FF, FB, digital zoom, etc.
<b>Alarm</b>	
Mode	Manual, motion, exception, smart event
Input	No
Output	No
<b>AI Function</b>	
Smart Motion Detection Performance	16CH
Perimeter Protection Performance	1CH
<b>Network</b>	
Interface	RJ 45 100Mbps × 1
Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP
Incoming Bandwidth	32Mbps (max. 64 Mbps)
Outgoing Bandwidth	80Mbps
Client Connection	Max. 10 users access

# TD-2168P-N2

## 16CH Hybrid DVR

### SPECIFICATIONS

Model	TD-2168P-N2
<b>Mobile Device</b>	
OS	iOS, Andriod
<b>Storage</b>	
HDD	SATA x 1, up to 10TB
<b>Backup</b>	
Local Backup	U disk, USB mobile HDD
Network Backup	Yes
<b>Port</b>	
RS 485	RS 485 x 1 (half-duplex)
USB	USB 2.0 x 2 ( in the rear panel )
Remote Controller	Optional
<b>Others</b>	
Power Supply	DC12V / 3A
Consumption	≤10W(without HDD )
Dimensions(mm)	255x 234x 42 ( W x D x H )
Working Environment	14°F ~ 122°F (-10~50°C, 10%~90% humidity)
Certificate	CE, FCC
Environmental Protection	Comply with Directive EU RoHS, WEEE, REACH