

# 5MP Fixed Eyeball Dome Network



MODEL **TI-NC405-XDA-36**



## KEY FEATURES

- High quality imaging with 5 MP resolution (2560x1944P)
- Low illumination 0.01Lux
- Day/Night, AWB/MWB,BLC, HLC, 2D/3D-DNR,Shutter, IR-CUT
- D-WDR,Mirror, rotate, Defogging
- Multiply Style OSD Overlay,Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 dual-stream media server
- Easy-to-use P2P Cloud service
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- RJ45 100mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Strong water-proof housing, IP66
- 18 pcs SMD Array IR Leds, IR distance 20-30 meters
- HD 3.6 mm fixed lens

# TI-NC405-XDA-36

## 5MP Fixed Eyeball Dome Network Camera

### SPECIFICATIONS

| 2592(H)×1944 (V)         | TI-NC405-XDA-36                                                                                                        |
|--------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>Camera</b>            |                                                                                                                        |
| Image Sensor             | 1/2.8" Sony CMOS                                                                                                       |
| Effective Pixels         | 5 megapixels                                                                                                           |
| Electronic Shutter       | AUTO, 1/25s ~ 1/100000s                                                                                                |
| Min. Illumination        | 0.01Lux@F1.2(AGC ON), 0Lux IR on                                                                                       |
| Day/Night                | Auto/Color/(B/W)/Timing                                                                                                |
| WDR                      | Digital WDR                                                                                                            |
| White Balance            | Auto /Manual                                                                                                           |
| AGC/BLC/HLC              | Support                                                                                                                |
| DNR                      | 2D/3D DNR                                                                                                              |
| Other                    | AGC,Motion Detection,Privacy Mask,Flip ,OSD overlay                                                                    |
| <b>Encode</b>            |                                                                                                                        |
| Video Standard           | H.264/H.265                                                                                                            |
| Video Resolution         | Main Stream:<br>25fps@5MP(2592x1944)/4MP(2592x1520)/3MP,<br>30fps@1080P/720P<br>Sub stream: 25fps@D1/VGA/360P/CIF, etc |
| Video Bitrates           | 512Kbps - 12Mbps, VBR/CBR                                                                                              |
| Audio Standard           | G.711-u/G.711-a                                                                                                        |
| Built-in Mic             | Optional                                                                                                               |
| OSD Overlay              | Title and Time overlay                                                                                                 |
| <b>IR Led</b>            |                                                                                                                        |
| IR Led                   | 18 pcs IR Led                                                                                                          |
| IR Distance              | 20-30M                                                                                                                 |
| <b>Lens</b>              |                                                                                                                        |
| Focal Length             | 3.6mm Fixed lens                                                                                                       |
| <b>Optional Function</b> |                                                                                                                        |
| PoE, audio               |                                                                                                                        |
| <b>Network Services</b>  |                                                                                                                        |
| Protocol                 | HTTP/RTSP/FTP/SMTP/DHCP/NTP/NFS, etc.                                                                                  |
| P2P                      | Yes                                                                                                                    |
| Web                      | IE, Firefox, (32bit ESR), etc.                                                                                         |
| Media                    | CMS, Android, iOS                                                                                                      |
| ONVIF                    | 17.06 compatible                                                                                                       |
| <b>General</b>           |                                                                                                                        |
| Network Port             | 1-RJ45, 100Mbps, POE optional                                                                                          |
| Power Supply             | 12 VDC ± 10%                                                                                                           |
| Power Consumption        | < 8 W                                                                                                                  |

# TI-NC405-XDA-2.8

5MP Fixed Eyeball Dome Network Camera

## DIMENSION

