

6MP 4X VeriFocal Dome Network Camera



MODEL **TI-NC416-4VDZA**



KEY FEATURES

- High quality imaging with 6 MP resolution (3072 x 2048)
- Ultra low illumination 0.01Lux
- Day/Night (ICR), AWB, 2D/3D-DNR, IR-CUT, Privacy Mask, Mirror
- D-WDR, Motion Detection, Human Detection, Vehicle Detection
- RTSP and Onvif 17.06 compatible
- H.265/H.264 dual-stream media server
- Easy-to-use P2P Cloud service
- Multi web browser, PC Client, mobile APP remote access
- RJ45 100mbps network port, IEEE802.3af PoE
- Lightning protection 4000V
- Support With human body detection & Vehicle Detection
- 18PCS SMD Array Led, IR distance : 75FT
- 2.8-12mm Motorized Veeri Focal Lens
- Water Proof : IP66
- Internal Microphone / SD Card Slot

TI-NC416-4VDZA

6MP 4X VeriFocal Dome Network Camera

SPECIFICATIONS

Model	TI-NC416-4VDZA
Camera	
Image Sensor	1/2.8" Sony CMOS
Effective Pixels	3072(H)×2048 (V)
Electronic Shutter	AUTO, 1/25s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON), 0Lux IR on
Day&Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
AGC/BLC/HLC	Support
DNR	2D/3D DNR
Other	Multi-lines OSD, Motion Detection, Privacy Mask, Mirror
Encode	
Video Compression	H.265/H.264
Video Resolution	Main Stream: 25fps@6MP(3072x2048)/5MP(2592x1944), 30fps@4MP/3MP/1080P/720P Sub stream: 30fps@D1/VGA/360P/CIF, etc.
Video Bitrates	64Kbps - 8Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a/AAC
Built-in Mic	Yes
Smart Event	Human Detection Vehicle Detection Motion Detection
IR Led	
IR Led	18PCS SMD array IR Led
IR Distance	25-30M
Lens	
Focal length	G711U/ 2.8-12mm Motorized lens G711A/AAC
Optional Function	
POE, Internal Microphone, etc	
Network Services	
Protocol	HTTP(S)/RTSP/RTMP/FTP/NFS/SMTP/DHCP/NTP, etc
P2P	Yes
Web	IE , Firefox 32bit ESR, etc
Media	CMS, Android, IOS
ONVIF	17.06 compatible

TI-NC416-4VDZA

6MP 4X VeriFocal Dome Network Camera

SPECIFICATIONS

Model	TI-NC416-4VDZA
Network Port	1-RJ45, 100Mbps, POE optional
Power Supply	12 VDC \pm 10%
Power Consumption	123*123*118(m < 5 W m)
Operating Temp	-22°F ~ 140°F (-30°C-(+60)°C), 10%-90%RH

DIMENSION

