

# 5MP Fixed Small Turret Network Camera



MODEL **TI-NC515-XDA-28**



## KEY FEATURES

- High quality imaging with 5 MP resolution
- Max. 2592\*1944 [5mp@25fps] (50Hz/60Hz)
- Support RTSP&Onvif (17.2 with profile S) Compatible with many third-party NVRs and CMS
- Support multiplay Web Browsers: IE/Firefox/Chrome/Safari etc.
- P2P Cloud service
- Free PC Client Software and Smartphone APP(P2P)
- Support Alarm Snapshot to Email and FTP
- Day/Night, AWB/MWB,BLC, 3D-DNR,Shutter, WDR,IR-CUT, D-WDR,Mirror, Image Flip etc.
- 2.8mm Fixed Lens
- 2pcs IR Array Leds, IR distance : 60FT
- Water-proof : IP66
- Built in MIC/ SD Card Slot/ Reset Button

# TI-NC515-XDA-28

## 5MP Fixed Small Turret Network Camera

### SPECIFICATIONS

Model	TI-NC515-XDA-28
<b>Camera</b>	
Image Sensor	1/2.8"Sony CMOS
Signal System	PAL/NTSC
Min. Illumination	Color: 0.05lux @(F1.2, AGC ON), 0 lux with IR
Shutter Time:	1/25 s to 1/10,000 s
Lens	2.8mm fixed lens
Day&Night	IR cut filter with auto switch
Image Enhancement	BLC/3D DNR/D-WDR
Motion Detection	Support
Intelligent Detection(AI)	Human Detection,Vehicle detection
Privacy Protection	Support(4 Self-customized Areas)
Wather-Proof	IP66
Illumination for Infrared Switching	1~5Lux
Infrared Wavelength	850nm
Mimimum Illumination	0 Lux(IR ON)
IR Range	2pcs Strong LED//20m IR
<b>Compression Standard</b>	
Video Compression	H.265/H.264
Video Bit Rate	512Kbps~6144Kbps(main stream H.265) 64kbps~2048Kbps(sub stream H.264)
Audio Compression	G711U/G711A
Dual Streams	Yes
<b>Image</b>	
Image Resolution:	2592*1944[5mp@25fps]
Frame Rate	25fps(5MP).MAX main stream 30fps (D1) .MAX sub stream
Image Settings	3D NR, D-WDR, Image Flip, Saturation, Brightness, Contrast, Sharpness adjustable via client software, web browser or Smartphone App
Day/Night Switch	EXT/Day/Night/Auto/Time
<b>Audio</b>	
Audio Compression	G711U/G711A/AAC
Audio Bitrate	64K(G711)/16k(AAC)
Built-in MIC	Yes
Volnume adjust	Yes

# TI-NC515-XDA-28

## 5MP Fixed Small Turret Network Camera

### SPECIFICATIONS

Model	TI-NC515-XDA-28
<b>Network</b>	
Network Protocols	HTTP, TCP/IP, IPv4/v6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, IP Search (Support P2P, NVR, NVS etc.)
System Compatibility	ONVIF (17.2 with profile S)
On-line Viewing	Max. Support 2 Users Simultaneously
<b>Interface</b>	
Communication Interface	1 RJ45 10M / 100M Ethernet Interface
RCA Audio Interface	RCA Audio input/output Interface (Optional)
Alarm in/out interface	Support (1ch) (Optional)
DC Power Plug	DC Power Female Interface
<b>General</b>	
Operating Conditions	14°F ~ 140°F (-10°C ~ 60°C)
	Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10% / PoE (802.3at/af)
Power Consumption	12 VDC ± 10%, Max Power Consumption Less than 8W (When the infrared lamps turn on)
Weight	1.1 lb
Dimension	4 3/8 (W) x 4 (H)