

5MP 5X Dual Light Turret PTZ Network Camera



MODEL_ **TI-NC515DL-XPZA**



KEY FEATURES

- 1/2.8" Sony CMOS sensor / 5X Dual Light full Color PTZ Turret Camera
- 5MP resolution 2596 x 1944P
- Low illumination 0.01Lux
- 5x optical zoom (2.7 -13.5m) Motorized Lens
- Smart Human and Vehicle Detection Alarm
- Colorful videos at night when human or Vehicle motion detection & alarm trigger
- Siren and Voice Warning, Strobe Light
- Day/Night, AWB/MWB, BLC, HLC, 2D/3D-DNR, Shutter, IR-CUT, D-WDR, Flip, Defogging
- Multiply Style OSD Overlay, Motion Detection, Privacy Mask
- RTSP and Onvif 17.06 compatible with many third-party NVR
- H.264/H.265 three-stream media server
- Support user authentication, video data encryption
- Support Alarm Snapshot to Email and FTP
- Free PC Client, Mobile APP remote access
- Lightning protection 4000V
- Strong water-proof housing IP66
- 4 pcs IR & Warmlight Leds, IR 120ft, Warm-light 90ft
- Built-in Mic and speaker, two-way audio

TI-NC515DL-XPZA

5MP 5X Dual Light Turret PTZ Network Camera

SPECIFICATIONS

Model	TI-NC515DL-XPZA
Camera	
Image Sensor	1/2.8" Sony CMOS
Effective Pixels	8 megapixels
Electronic Shutter	AUTO, 1/10s ~ 1/100000s
Min. Illumination	0.01Lux@F1.2(AGC ON)
Day/Night	Auto/Color/(B/W)/Timing
WDR	Digital WDR
White Balance	Auto/Manual
BLC /HLC	Support
DNR	2D/3D DNR
Other	Image adjust , Flip
Encode	
Video Standard	H.265/H.265+/H.264
Video Resolution	MainStream:20fps@8MP(3840x2160), 30fps@6MP(3072x2048)/5MP(2592x1944)/4MP/3MP/1080P/720P,etc. Sub stream: 720x480/VGA(640x480)/360P/QVGA@30fps,etc. Third stream:1080P/720P/CIF@10fps
Video Bitrates	512Kbps - 12Mbps, VBR/CBR
Audio Standard	G.711-u/G.711-a/AAC
Audio	Two way audio: Built-in Mic. & loudspeaker
Smart Detection	Smart Human & Vehicle Detection
Illuminator	
Led	4pcs IR & Warmlight Leds
Distance	40 m (IR), 30 m (Warm light)
Lens	
Focal length	2.7-13.5mm
Zoom	5x optical zoom
Function	
SD Storage	Build in Micro SD Card Slot, Max 512GB
Reset	Build in Reset Button
PTZ	
Pan/Tilt Range	Pan: 0° ~ 280°; Tilt: 0° ~ 90°
Preset Point	10
Control Speed	Pan: 15° /s; Tilt: 15° /s
Guard Position	Support
Power-off Recovery	Support

TI-NC515DL-XPZA

5MP 5X Dual Light Turret PTZ Network Camera

SPECIFICATIONS

Model	TI-NC515DL-XPZA
Network	
Network Protocols	Http/Https, TCP/IP, IPv4/v6, UPNP, RTSP/RTMP,FTP, UDP, SMTP, NTP, DHCP, DNS, DDNS,IP Search(Support P2P, NVR, NVS etc.)
General Function	Anti-Flicker, heartbeat, password protection, privacy mask, Watermark
System Compatibility	ONVIF(17.2 with profile S)
On-line Viewing	Max. Support 2 User Max. Support 2 Users Simultaneously s Simultaneously
Interface	
Communication Interface	1 RJ45 10M / 100M Ethernet Interface
Audio Interface	Build-in MIC and Speaker
Alarm in/out interface	Support (1ch) (Optional)
SD card interface	Support TF card (micro TF card, up to 128G) (Optional)
DC Power Plug	DC Power Femate Interface/POE(optional)
General	
Operating Conditions	14°F~ 140°F (-10 °C ~ 60 °C)
	Humidity 95% or less (non-condensing)
Power Supply	12 V DC $\pm$ 10%/PoE(802.3at/af)
Power Consumption	12 VDC $\pm$ 10%, Max Power Comsumption Less than 8W (When the infrared lamps turn on)
Size	Φ 4.72441(inch) x 4.33071(inch)
Weight	0.56KG

PHYSICAL INTERFACE

