

Todaair

Product Specification

TD-MRT45 V40

Date:10th/Feb./2023



Product Overview

TD-MRT45 V40 is a Wi-Fi 6 developed by Todaair, which can support up to 1800Mbps commercial AP coverage or home Wi-Fi coverage MESH routers.

Supports desktop placement, ceiling mounting and outdoor wall hanging waterproof installation.

Features

- Support 802.11 b/g/n/ac/ax 2x2:2
- Support 802.11 a/n/ac/ax 2x2:2
- 2 * 1000Mbps RJ45
- IEEE802.3at/af
- Weatherproof and anti-UV
- Dual frequency gigabit, support Wi-Fi 6
- Support Todaair APP and cloud management, intelligent operation and maintenance
- Support for outdoor scenario use
- Operating Temperature: - 30°C~ 50°C
- The WAN port supports POE function

Hardware Specification

Chipset	MT7621AT/A+MT7975DN+MT7905DN			
DRAM	DDR3 128MByte			
FLASH	16MByte			
Power Amplifier IC	2.4G / 5.8G MT7905DN			
Wired Interface	10/100/1000Mbps WAN*1 (POE) LAN*1			
Date Rate 2.4G	580Mbps			
Date Rate 5.8G	1201Mbps			
Modulation Mode	OFDM/BPSK/QPSK/CCK/DQPSK/DBPSK			
Standard	IEEE802.11a,IEEE802.11n,IEEE802.11g,IEEE802.11b,IEEE802.3u,IEEE802.3af,IEEE802.11ac,IEEE 802.11ax			
Frequency Range	2.4G 2412Mhz~2472Mhz / 5.8G 5180Mhz~5825Mhz			
Power Consumption	≤15W			
Power	POE 48V 0.5A			
RF Power @25°C±2Db 2.4G	802.11b	20±2dBm		
	802.11g	6-24Mbps	20±2dBm	
		36-48Mbps	20±2dBm	
		54Mbps	20±2dBm	
	802.11n	HT20	MCS 7	20±2dBm
		HT40	MCS 7	20±2dBm
	802.11ax	HT20	MCS0/12	

		HT40	MCS2/14	
RF Power @25°C±2dB 5.8G	802.11a	6-24Mbps	20±2dBm	
		36-48Mbps	18±2dBm	
		54Mbps	17±2dBm	
	802.11ac	HT20	MCS 0-3	20±2dBm
			MCS 4	20±2dBm
			MCS 5	19±2dBm
			MCS 6	18±2dBm
			MCS 7	18±2dBm
		HT40	MCS 0-3	20±2dBm
			MCS 4	19±2dBm
			MCS 5	19±2dBm
			MCS 6	18±2dBm
		HT80	MCS 3	20±2dBm
			MCS 4	19±2dBm
			MCS 5	19±2dBm
			MCS 6	18±2dBm
			MCS 7	18±2dBm
	802.11ax	HT80	MCS0/12	17±2dBm
			MCS6/18	17±2dBm
Sensitivity 2.4G	IEEE 802.11b	11Mbps ≤ -85dBm		
	IEEE 802.11g	54Mbps ≤ -70dBm		

	802.11n	HT20	MCS 7 ≤ -65dBm
		HT40	MCS 7 ≤ -62dBm
Sensitivity 5.8G	802.11a	6Mbps ≤ -89 ; 54Mbps ≤ -73	
	802.11ac	HT20	MCS 0 ≤ -94; MCS 7 ≤ -76
		HT40	MCS 0 ≤ -92; MCS 7 ≤ -76
		HT80	MCS 0 ≤ -90; MCS 7 ≤ -67
	802.11ax	HT80	MCS0 ≤ -85; MCS 12 ≤ -60
Antenna System	Frequency Range	2.4G Antenna 2412Mhz~2484Mhz 5.8G Antenna 5150Mhz~5850Mhz	
	Polarization	Onmidirectional	
	Gain	4DBi*4	
Operating/Storage Environment	Operating Temperature	-30 ~ 50℃	
	Storage Temperature	-50 ~ 80℃	
	Humidity (Non-concentrated)	≤95% (Non-condensed)	
Size & Weight	Bare Metal Size : 70*170mm		
	Bare Weight : 0.45kg		

Todaair



Todaair APP

JIANGMEN TODAAIR ELECTRONIC CO.,LTD

☎: +86-0750-3135725

✉: www.todaair.com