

# 5MP Fixed Pinhole Lens Network Camera



MODEL **TI-NC515-MP37**



## KEY FEATURES

- 1/2.8" SONY COMS Sensor
- 5MP HD Resolution Output (Max. 2592×1944 @25fps, 50/60Hz)
- Day/Night, AWB/MWB, BLC, D-WDR, 3D-DNR, Shutter, IR-CUT
- Mirror, Image Flip (etc. functions)
- RTSP & ONVIF 17.2 (Profile S) Compatible (3rd-party NVRs/CMS)
- H.265 / H.264
- P2P Cloud Service
- Multi Web Browsers: IE / Firefox / Chrome / Safari
- Free PC Client Software & Smartphone APP (P2P)
- Alarm Snapshot to Email & FTP
- 3.7mm Pinhole Lens
- Built-in Mic / Out Optional (RCA Cable Interface)
- Power: 12V DC & PoE

# TI-NC515-MP37

## 5MP Fixed Pinhole Lens Network Camera

### SPECIFICATIONS

Model	TI-NC515-MP37
<b>Camera</b>	
Image Sensor	1/2.8" Sony CMOS
Signal System	PAL/NTSC
Shutter Time	1/25 s to 1/10,000 s
Lens	3.7mm Pinhole Lens
Image Enhancement	BLC/3DDNR/D-WDR/WDR
Motion Detection	Support
Intelligent Detection (AI)	Human Detection
Privacy Protection	Support (4 Self-customized Areas)
Water-Proof	/
<b>Compression Standard</b>	
Video Compression	H.265/H.264
Video Bit Rate	512Kbps~6144Kbps (main stream H.265) 64kbps~1024Kbps (sub stream H.265)
Audio Compression	G711U/G711A/AAC
Dual Streams	Yes
Triple Streams	No
<b>Image</b>	
Max. Image Resolution	2592*1944@25fps (5MP)/2560*1440@30fps/1920*1080@30fps
Frame Rate	25fps (5MP).MAX main stream 25fps (D1).MAX sub stream
Image Settings	3DNR, D-WDR, Image Flip, Saturation, Brightness, Contrast, Sharpness adjustable via client software, web browser or Smartphone App
<b>Audio</b>	
Line IN/line OUT	Support (1ch)
Build-in MIC	Optional
Volume adjust	Yes
<b>Network</b>	
Network Protocols	HTTP, TCP/IP, IPv4/v6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, RTMP, IP Search (Support P2P, NVR, NVS etc.)
System Compatibility	ONVIF (17.2 with profile S)
On-line Viewing	Max. Support 2 Users Simultaneously
<b>Interface</b>	
Communication Interface	1 RJ45 10M/100M Ethernet Interface
RCA Audio Interface	RCA Audio input/output Interface (Optional)
Alarm in/out interface	Support (1ch) (Optional)
DC Power Plug	DC Power Female Interface

# TI-NC515-MP37

## 5MP Fixed Pinhole Lens Network Camera

### SPECIFICATIONS

Model	TI-NC515-MP37
<b>General</b>	
Operating Conditions	14 °F ~ 140 °F (-10 °C ~ 60 °C)
	Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 10%/PoE
Power Consumption	12 VDC ± 10%, Max Power Consumption Less than 8W (When the infrared lamps turn on)
Weight	0.44 lb (0.2KG)
FCL box size	21.65 × 16.14 × 9.06 inch (550*410*230 mm)