8MP LITE XVR 8CH (5 IN 1)



MODEL _ **TI-XR108-4**

KEY FEATURES

- Support H.265/H.264 video formats
- Support audio over coaxial cable(only for TVI cameras)
- Support TVI, AHD, CVI, CVBS, IP cameras with adaptive access
- 8-channel BNC input
- Support 1-ch CVBS output, 1-ch VGA output, 1-ch HDMI output at up to 4K(3840 x 2160)
- HDMI and VGA simultaneous output
- Long transmission distance over coaxial cable
- Support mainstream cameras of ONVIF and RTSP protocols

TI-XR108-4

8MP LITE XVR 8CH (5 IN 1)

SPECIFICATIONS

Model	TI-XR108-4	
Video/Audio Input		
Analog Video Input	8-ch, BNC	
IP Video Input	4-ch(only IP up to 12ch), each channel up to 8MP	
Supported Analog Camera Types	**Support AHD, TVI, CVI input:** 8MP@15fps 5MP@20fps 4MP@30fps 1080P@30fps 720P@30fps **Support CVBS input**	
Audio Input	1Ch, RCA	
Audio Compression	G.711U	
Video/Audio Output		
CVBS Output	1-ch, BNC	
VGA Output	1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
HDMI Output	3840 x 2160/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz	
Audio Output	1-ch, RCA	
Synchronous Playback	8	
Live view display	HDMI/VGA: 1/4/6/8/9/16	
Two-way Audio	1-ch, RCA	
Network		
Incoming Bandwidth	40Mbps (Up to 56Mbps after all analog channel conversion)	
Outgoing Bandwidth	64Mbps	
Remote Users	128	
Protocols	TCP/IP, P2P, UPnP, DHCP, HTTP, HTTPS, DNS, DDNS, SMTP	
Browser	IE(IE10/11) for Windows / Firefox (version 52.0 and above) for Windows Chrome(version 45 and above) for Windows / Edge(version 79 and above) for Windows	
Encoding		
Recording Resolution	8MP Lite/5MP Lite/4MP Lite /1080P/720P/CIF	
Recording	**Main stream**	**Sub stream**
	8MP Lite@8fps	D1@8fps
Frame Rate	5MP Lite @12fps	D1@12fps
	4MP Lite@15fps	D1@15fps
Audio Sample Rate	8KHz,16 bit per channel	
Audio Bit Rate	64Kbps per channel	
Decoding		
Capability	Analog: 8 x 8MP Lite@8, 8x 5MP Lite@12, 8x 4MP Lite@15, 8x 1080P@15 IP: 1 x 8MP@30, 2 x 4MP@30, 4 x 1080P@30	

TI-XR108-4

8MP LITE XVR 8CH (5 IN 1)

SPECIFICATIONS

Model	TI-XR108-4
Hard Disk	
SATA	1 SATA interface
Capacity	Up to 8TB for each HDD (The maximum HDD capacity varies with environment temperature)
General Alarm	
General Alarm	Motion detection
Alert Alarm	IP Conflict, Network Disconnected, Disk offline, Disk Abnormal, Illegal Access, Hard Disk Space Low, Hard Disk Full, Recording/Snapshot Abnormal
External Interface	
Network Interface	1 RJ45 10M/100M self-adaptive Ethernet Interface
USB Interface	Rear panel: 2 x USB2.0
RS485	1
Alarm In	4-ch
Alarm Out	1-ch
General	
Power Supply	12V DC Power Consumption: ≤ 10 W(without HDD)
Working Environment	14°F ~ 131°F (-10°C ~ + 55°C), Humidity ≤ 90% RH(non-condensing)
Dimensions(W×D×H)	10.2″ × 8.9″×1.8″ (260mm ×226mm× 47mm)
Weight (without HDD)	2.42lb (≤1.1 Kg)
Certification	
Certification	UL /CE /FCC /RoHS /WEEE

Dimensions



